

UNIVERSALES | UNIVERSAL RANGE | GAMME UNIVERSELLE | GAMMA UNIVERSALE | GAMA UNIVERSAL

REFERENCIA	Ø VARILLA (mm)	Ø CUERPO (mm)	LONGITUD ABIERTO (mm)	FUERZA (Newtons)	RECORRIDO (mm)
200 mm					
1840.0050053	8	18	200	200	60
1840.0050111	8	18	200	300	60
1840.0050001	8	18	200	350	55
1840.0050128	8	18	200	400	60
1840.0050021	8	18	200	450	60
1840.0050093	8	18	200	500	60
1840.0050011	8	18	200	550	55
1840.0050070	8	18	200	650	60
250 mm					
1840.0050145	8	18	250	100	80
1840.0050054	8	18	250	200	85
1840.0050112	8	18	250	300	85
1840.0050002	8	18	250	350	80
1840.0050129	8	18	250	400	85
1840.0050022	8	18	250	450	85
1840.0050094	8	18	250	500	80
1840.0050012	8	18	250	550	80
1840.0050146	8	18	250	600	80
1840.0050071	8	18	250	650	85
300 mm					
1840.0050147	8	18	300	150	110
1840.0050055	8	18	300	200	110
1840.0050113	8	18	300	300	110
1840.0050003	8	18	300	350	105
1840.0050130	8	18	300	400	110
1840.0050023	8	18	300	450	110
1840.0050095	8	18	300	500	105
1840.0050013	8	18	300	550	105
1840.0050072	8	18	300	650	110
325 mm					
1840.0050056	8	18	325	200	120
1840.0050114	8	18	325	300	120
1840.0050031	8	18	325	350	120
1840.0050131	8	18	325	400	120
1840.0050045	8	18	325	450	120
1840.0050038	8	18	325	550	120
1840.0050073	8	18	325	650	120
350 mm					
1840.0050057	8	18	350	200	135
1840.0050148	8	18	350	250	130
1840.0050115	8	18	350	300	135
1840.0050004	8	18	350	350	130
1840.0050132	8	18	350	400	135
1840.0050024	8	18	350	450	135
1840.0050096	8	18	350	500	135
1840.0050014	8	18	350	550	130
1840.0050074	8	18	350	650	135
1840.0050087	8	18	350	750	125
375 mm					
1840.0050058	8	18	375	200	145
1840.0050116	8	18	375	300	150
1840.0050032	8	18	375	350	145
1840.0050133	8	18	375	400	150
1840.0050046	8	18	375	450	145
1840.0050039	8	18	375	550	145
1840.0050075	8	18	375	650	145

REFERENCIA	Ø VARILLA (mm)	Ø CUERPO (mm)	LONGITUD ABIERTO (mm)	FUERZA (Newtons)	RECORRIDO (mm)
400 mm					
1840.0050149	8	18	400	150	160
1840.0050059	8	18	400	200	160
1840.0050150	8	18	400	250	160
1840.0050117	8	18	400	300	160
1840.0050005	8	18	400	350	155
1840.0050134	8	18	400	400	160
1840.0050025	8	18	400	450	160
1840.0050151	8	18	400	500	160
1840.0050015	8	18	400	550	155
1840.0050076	8	18	400	650	160
1840.0050152	8	18	400	700	160
425 mm					
1840.0050060	8	18	425	200	170
1840.0050118	8	18	425	300	175
1840.0050033	8	18	425	350	170
1840.0050135	8	18	425	400	170
1840.0050047	8	18	425	450	170
1840.0050040	8	18	425	550	170
1840.0050077	8	18	425	650	170
450 mm					
1840.0050153	8	18	450	150	180
1840.0050061	8	18	450	200	185
1840.0050119	8	18	450	300	185
1840.0050006	8	18	450	350	180
1840.0050136	8	18	450	400	185
1840.0050026	8	18	450	450	185
1840.0050097	8	18	450	500	180
1840.0050016	8	18	450	550	180
1840.0050098	8	18	450	600	180
1840.0050078	8	18	450	650	185
1840.0050154	8	18	450	700	180
1840.0050088	8	18	450	750	185
475 mm					
1840.0050062	8	18	475	200	195
1840.0050120	8	18	475	300	200
1840.0050034	8	18	475	350	195
1840.0050137	8	18	475	400	200
1840.0050048	8	18	475	450	195
1840.0050041	8	18	475	550	195
1840.0050079	8	18	475	650	195
500 mm					
1840.0050155	8	18	500	150	200
1840.0050063	8	18	500	200	210
1840.0050156	8	18	500	250	200
1840.0050121	8	18	500	300	210
1840.0050007	8	18	500	350	205
1840.0050138	8	18	500	400	210
1840.0050027	8	18	500	450	210
1840.0050157	8	18	500	500	200
1840.0050017	8	18	500	550	205
1840.0050158	8	18	500	600	200
1840.0050080	8	18	500	650	210
1840.0050089	8	18	500	750	210
525 mm					
1840.0050064	8	18	525	200	220
1840.0050122	8	18	525	300	225
1840.0050035	8	18	525	350	220
1840.0050139	8	18	525	400	225
1840.0050049	8	18	525	450	220
1840.0050042	8	18	525	550	220
1840.0050081	8	18	525	650	220

UNIVERSALES | UNIVERSAL RANGE | GAMME UNIVERSELLE | GAMMA UNIVERSALE | GAMA UNIVERSAL

REFERENCIA	Ø VARILLA (mm)	Ø CUERPO (mm)	LONGITUD ABIERTO (mm)	FUERZA (Newtons)	RECORRIDO (mm)
550 mm					
1840.0050065	8	18	550	200	235
1840.0050159	8	18	550	250	230
1840.0050123	8	18	550	300	235
1840.0050008	8	18	550	350	230
1840.0050140	8	18	550	400	235
1840.0050028	8	18	550	450	235
1840.0050099	8	18	550	500	235
1840.0050018	8	18	550	550	230
1840.0050100	8	18	550	600	235
1840.0050082	8	18	550	650	235
1840.0050090	8	18	550	750	235
1840.0050160	8	19	550	800	230
575 mm					
1840.0050066	8	18	575	200	245
1840.0050124	8	18	575	300	250
1840.0050036	8	18	575	350	245
1840.0050141	8	18	575	400	245
1840.0050050	8	18	575	450	245
1840.0050043	8	18	575	550	245
1840.0050083	8	18	575	650	245
600 mm					
1840.0050067	8	18	600	200	260
1840.0050125	8	18	600	300	260
1840.0050009	8	18	600	350	255
1840.0050142	8	18	600	400	260
1840.0050029	8	18	600	450	260
1840.0050161	8	18	600	500	250
1840.0050019	8	18	600	550	255
1840.0050162	8	18	600	600	250
1840.0050084	8	18	600	650	260
1840.0050091	8	18	600	750	260
1840.0050163	8	19	600	800	250
625 mm					
1840.0050068	8	18	625	200	270
1840.0050126	8	18	625	300	275
1840.0050037	8	18	625	350	270
1840.0050143	8	18	625	400	270
1840.0050051	8	18	625	450	270
1840.0050044	8	18	625	550	270
1840.0050085	8	18	625	650	270

REFERENCIA	Ø VARILLA (mm)	Ø CUERPO (mm)	LONGITUD ABIERTO (mm)	FUERZA (Newtons)	RECORRIDO (mm)
650 mm					
1840.0050069	8	18	650	200	285
1840.0050127	8	18	650	300	285
1840.0050010	8	18	650	350	280
1840.0050144	8	18	650	400	285
1840.0050030	8	18	650	450	285
1840.0050101	8	18	650	500	280
1840.0050020	8	18	650	550	280
1840.0050102	8	18	650	600	280
1840.0050086	8	18	650	650	285
1840.0050092	8	18	650	750	285
700 mm					
1840.0050103	8	18	700	200	300
1840.0050164	8	18	700	250	300
1840.0050104	8	18	700	350	300
1840.0050165	8	18	700	450	300
1840.0050105	8	18	700	500	300
1840.0050106	8	18	700	600	300
1840.0050166	8	18	700	650	300
1840.0050167	8	19	700	800	300
750 mm					
1840.0050107	8	18	750	200	325
1840.0050108	8	18	750	350	325
1840.0050109	8	18	750	500	325
1840.0050168	8	18	750	550	330
1840.0050169	8	18	750	650	330
1840.0050110	8	18	750	600	325
800 mm					
1840.0050170	8	18	800	550	360
1840.0060001	RÓTULA VARILLA 8MM				
1840.0060002	OJAL VARILLA 8MM				
1840.0060003	CASQUILLO ALARGADOR VARILLA 8MM				
1840.0060004	RÓTULA VARILLA 8MM				
1840.0060005	RÓTULA VARILLA 8MM				

**Resortes de gas nitrógeno.
Cuerpo en acero esmaltado.**

